



Marine Hydraulic Systems

Sailtec Inc.

2930 Conger Court, Oshkosh, WI 54904, U.S.A.

Phone: 920-233-4242

Fax: 920-233-8767

Email: customerservice@sailtec.com

Web: www.sailtec.com

## Specification Table

### Remote Panel Pump Overview

| MODEL               | DESCRIPTION        | PANEL DIMENSIONS<br>H X W X D |                 | SPEED*          |      | SPEED** | FEATURES/COMMENTS   |
|---------------------|--------------------|-------------------------------|-----------------|-----------------|------|---------|---|
|                     |                    | INCH                          | MM              | IN <sup>3</sup> | ML   |         |   |
| T7 Panel            | Single Acting Pump | 3.5 x 6.5 x 2.5               | 89 x 165 x 63   | 0.16            | 2.6  | 84      | No gauge. Handle projects. 15" from panel face.   |
| T6 Panel            | Single Acting Pump | 6.1 x 6.1 x 2.5               | 157 x 156 x 64  | 0.16            | 2.6  | 84      | Gauge. Handle sweeps side to side. Very compact.  |
| T5 Panel            | Double Acting Pump | 8.6 x 6 x 4.5                 | 219 x 152 x 114 | 0.3             | 5    | 44      | Gauge. Handle sweeps side to side. Currently the fastest panel in the industry.         |
| T5HS Panel          | Double Acting Pump | 8.8 x 10 x 4.5                | 223 x 254 x 114 | 0.34            | 5.5  | 39      | Larger 2" dia. gauge than T5. Attractive design. Fast acting. Handle location improved. |
| M Panel             | Double Acting Pump | 9.0 x 7 x 2.5                 | 229 x 178 x 63  | 0.38            | 6.2  | 35      | Large 2" dia. gauge. Shallow depth. Attractive. Fastest pump available to market.       |
| TX6 Panel           | Single Acting Pump | 8.8 x 7 x 2.5                 | 223 x 178 x 63  | 0.18            | 2.9  | 75      | Large 2 " dia. gauge. Shallow depth. Attractive.  |
| Two Speed Autoshift |                    | 8.8 x 11.0 x 5.0              | 223 x 279 x 127 | 0.75            | 12.2 | 19      | Operates full capacity to 2000 psi and half capacity from 2000 to 5000 psi.             |

Data subject to change

\*Volume of oil per pump strokes. \*\*Number of strokes to retract a -12 cylinder ram 10".